



# ADW-E

## PRODUCT INFORMATION

- ✓ OIML-R76 and EC Class III Type Approved
- ✓ Washdown Construction: Designed According to IP 66
- ✓ Sealed Electronics
- ✓ Moisture Detection Desiccant Inside
- ✓ Two Types of Display Version: ADW-C = LCD and ADW-E = LED
- ✓ Supports 1/6000 to 1/7500 Display Resolution for Non-OIML Applications
- ✓ Support Metric and imperial Weight Units and Conversion
- ✓ Weight Check Functions with HI-OK-LO indicators and Buzzer Output, User Programmable Buzzer Output Configuration, and Automatic Tare Function
- ✓ Power ON Zero Tracking, Manual Zero and Auto Calibration Functions
- ✓ Protection Devices against Overload and Shock
- ✓ Low Battery Indicator and Charging Status Indicator
- ✓ Stainless Steel Platter Cover, Adjustable Feet, Built-in Rechargeable Battery, Power Adaptor and Bubble Level Included
- ✓ Long Rechargeable Battery Operating Time: ADW-C = 120 Hours Plus and ADW-E = 80 Hours Plus
- ✓ Platter size: 215 x 250 mm
- ✓ Options available: RS-232 Interface



| Model   | Capacity | Readability |
|---------|----------|-------------|
| ADW-3E  | 3 kg     | 1 g         |
| ADW-6E  | 6 kg     | 2 g         |
| ADW-15E | 15 kg    | 5 g         |
| ADW-30E | 30 kg    | 10 g        |



**UNIVERSAL WEIGHT ELECTRONICS CO., LTD.**

4th FLOOR, NO.53, BAOXING ROAD, XINDIAN DISTRICT, NEW TAIPEI CITY 231, TAIWAN (R.O.C)

+886-2-29180121 | int@uwe.com.tw | www.uwe.com.tw